SÄKER

CLOSED CAB FORKLIFTS

FD70

7 Ton Diesel Airconditioned

FD30-RT

3 Ton Diesel Rough Terrain

ISUZU ENGINES

	Characteristics		FD70	FD30-RT
1	Model			
2	Rated capacity	kg	7000	3000
3	Lift height	mm	3000	3000
4	Load center distance	mm	600	500
5	Free lift	mm	150	200
6	Wheel, number Front/Rear(X=Driven)		4x/2	2x/2
7	Speed Travel	km/h	30	22
8	Speed Lifting Full Load	mm/s	460	450
9	Turning radius	mm	3350	2750
10	Ground clearance (without load)	mm	200	250
11	Total length	mm	3560	3060
12	Overall width	mm	2010	1604
13	Overall height (mast)	mm	2500	2115
14	Wheelbase	mm	2250	1835
15	Minimal aisle width	mm	3040	2615
16	Fork size (LxWxT)	mm	1520 x 150 x 70	1070 x 125 x 45
17	Fork adjustment distance	mm	-	-
18	Service weight	kg	9750	4800
19	Front overhang (Wheel centre to fork face)	mm	595	601
20	Rear overhang	mm	-	-
21	Mast tilt angle F/R		6°/12°	10°/12°
22	Max drawbar pull, laden	N	18%	32%
23	Max gradeability (Full load)	%	20	16
24	Braking distance (without load)	m	-	-
	Engine		Fawde 6 Cyl Diesel	Isuzu 4 Cyl Diesel
1	Model		CA6110	4JG2
2	Rated power/Rated Speed	KW/RPM	85/2000	46/2450
3	Max.Torque/Rated Speed	N.m/RPM	450/1400-1500	186.3/1600-1800
	Tyres		P/P	P/P
1	Tyre front size		8.25-15PR	14-17.5-14PR
2	Tyre front pressure		-	-
3	Tyre rear size		8.25-15PR	27x10-12-12PR
4	Tyre rear pressure		-	-

MAIN CHARACTERISTICS

- Airconditioned enclosed cab
- Powerful 85kW engine
- 2 Spd powershift transmission
- 2-Stage 3m mast
- 1520mm fork
- Side shift forks

- Isuzu 4JG2 46kw engine
- 2 Spd powershift transmission
- 2-Stage 3m Mast
- 1070mm Fork
- Side Shifter

WAHA EQUIPMENT

www.waha.co.za

Showroom: 578A 16th Road, Midrand, Jhb • **Office**: 011 574 5728
Will - 076 037 9516 • Alec - 060 998 3798 • Darren - 083 250 8481